

Line monitor

LM-400



Accessory: AC cable, Rack-mount hardware



Rear panel

It is possible to monitor 4 VTR by space-saving.

4 channel design to support a medium-size and a large-scale editing room. Video can be changed at the same time. It can find which VTR is monitored at a glance.

Independent monitor of L/R is possible.

Balance feature is built-in to monitor L/R. It made the monitor only of the voice in the field and the monitor only of the narration possible by this feature.

External speaker can be connected, too.

Phase checking function built-in

It supports phase trouble (cable polarity reverse) of the recorded stereo sound. By the phase checking function, in case of being a signal with normal phase (green LED), NORMAL lights up. If phase is different (red LED), INVERT lights up.

LM-400 Specifications

Input part	Canon 3P male 2CH (stereo)	x4
	BNC	x4
Output part	Canon 3P female 2CH (stereo)	x4
	BNC	x4
Function	Video Audio input change	x1
	Load change	600ohm/open x4
	Level change	+4dB/0dB x4
	VU meter	L, R x each1
	Phase display	CH A - CH D x1
	Speaker	L, R x each1
	VOL volume adjustment	x1
Power	Power	AC100V
General	Dimension	430x88x220mm (WxHxD)
	Weight	approx. 3kg
Accessory	AC cable, Rack-mount hardware	