

# PROTECH®



***Iris control equipped with  
Open control,  
Closed control***

## **AL-500SET**

***Iris zoom remocon***

Accessory: IF box, control cable (2m)

**Iris zoom lens remote control which improved and did a renewal in the operability**

**Iris control improved operability and gets renewed.**

It is possible to set Iris's opening maximum and minimum value beforehand. Non step variable zoom lens control function is built-in. It is equipped with the REC trigger.

The change switch corresponds to Canon lens and Fujinon lens.



**Outward appearance**



**Option**



**ALC-530**

**30m extension cable  
for AL-500SET**

**Composition**

### AL-500 Specifications

|         |                |   |
|---------|----------------|---|
| General | Adaptable lens | Canon / Fujinon(except some models)<br>As the shape of the connector of Fujinon lens for broadcast is different, please contact us. |
|         | OPEN LIMIT     | Limitation on F value the open side   |
|         | CLOSE LIMIT    | Maximum F value limitation  |
|         | VTR switch     | REC start/stop  |
|         | SLOW FAST      | SLOW: Zoom lens speed is slow.<br>FAST: Zoom lens is high-speed.  |
|         | WIDE TELE      | WIDE: wide angle side, TELE: telephotographic side  |
|         | CF switch      | Canon/Fujinon change  |
|         | Dimension      | 47 x 130 x 50mm (WxHxD)   |
|         | Weight         | approx. 210g (main unit)  |



**Non step variable zoom  
remocon, bestseller**

## AS-520

**Zoom remocon**

Accessory: IF box, control cable (2m)



**Installation to Pan stick is simple.**

It is the non step variable zoom remocon and can switch slow / first. It has REC trigger and return function. The change switch corresponds to Canon lens and Fujinon lens.

**Outward appearance**



Extension cable for AS-520,  
10m

**ASC-10**

Zoom remocon extension  
cable, 10m



Extension cable for AS-520,  
30m

**ASC-30**

Zoom remocon extension  
cable, 30m



Extension cable for AS-520,  
20m

**ASC-20**

Zoom remocon extension  
cable, 20m

### AS-520 Specifications

|                 |                |   |
|-----------------|----------------|---|
| General         | Adaptable lens | Canon / Fujinon(except some models)   |
|                 | VTR SW         | REC start/stop (RET SW switching is possible)                                 |
|                 | RET SW         | Return video can be seen while pressing SW.<br>(VTR SW switching is possible) |
|                 | SLOW FAST      | SLOW: Zoom lens speed is slow.<br>FAST: Zoom lens is high-speed.              |
|                 | CF SW          | Canon/Fujinon change  |
|                 | Dimension      | 45 x 95 x 41mm (WxHxD)  |
|                 | Weight         | approx. 215g  |
|                 | Option         | Extension cable   |
| Cnversion cable |                | 8PIN->12PIN conversion cable (for Fujinon broadcast lens)                     |