

# PROTECH®



**Iris control equipped with  
Open control,  
Closed control**

## **AL-500SET**

**Iris Zoom Control**

Accessory: IF box, control cable (2m)

**Iris zoom lens remote control which improved and did a renewal in the operability**

**Iris control improved operability and gets renewed.**

It is possible to set Iris's opening maximum and minimum value beforehand. Non step variable zoom lens control function is built-in. It is equipped with the REC trigger.

The change switch corresponds to Canon lens and Fujinon lens.



### Outward appearance

### Option



**Extension Cable 30m**

### Composition

#### AL-500 Specifications

General	Adaptable lens	Canon / Fujinon(except some models) As the shape of the connector of Fujinon lens for broadcast is different, please contact us.
	OPEN LIMIT	Limitation on F value the open side
	CLOSE LIMIT	Maximum F value limitation
	VTR switch	REC start/stop
	SLOW FAST	SLOW: Zoom lens speed is slow. FAST: Zoom lens is high-speed.
	WIDE TELE	WIDE: wide angle side, TELE: telephotographic side
	CF switch	Canon/Fujinon change
	Dimension	47 x 130 x 50mm (WxHxD)
	Weight	approx. 210g (main unit)



**Non step variable zoom control, bestseller**

## AS-520

### Zoom Control

Accessory: IF box, control cable (2m)



### Installation to Pan stick is simple.

It is the non step variable zoom control and can switch slow / first. It has REC trigger and return function. The change switch corresponds to Canon lens and Fujinon lens.

### Outward appearance



### Option



**Extension Cable 10m**

**ASC-10**

**Zoom control extension cable, 10m**



**Extension Cable 30m**

**ASC-30**

**Zoom control extension cable, 30m**



**Extension Cable 20m**

**ASC-20**

**Zoom control extension cable, 20m**

### AS-520 Specifications

General	Adaptable lens	Canon / Fujinon(except some models)
	VTR SW	REC start/stop (RET SW switching is possible)
	RET SW	Return video can be seen while pressing SW. (VTR SW switching is possible)
	SLOW FAST	SLOW: Zoom lens speed is slow. FAST: Zoom lens is high-speed.
	CF SW	Canon/Fujinon change
	Dimension	45 x 95 x 41 mm (WxHxD)
	Weight	approx. 215g
Option	Extension cable	ASC-10 (10m), ASC-20 (20m), ASC-30 (30m)
	Conversion cable	8PIN→12PIN conversion cable (for Fujinon broadcast lens)